

**INSUL-MATE™**  
**1 1/4" x 1/4" Corrugated Sheeting**

**DESCRIPTION/SPECIFICATIONS**

RPR Products Insul-Mate™ 1 1/4" x 1/4" corrugated sheets are manufactured to form a continuous pattern of 1/4" high ribs on 1 1/4" centers with both longitudinal edges of the sheet formed down allowing the sheet to be installed without alternating the ends of the sheet. This profile is designed for superior strength for use in a number of applications such as tanks, vessels, towers, equipment, etc.



- Alloys:
- Aluminum 3003, 3105
  - Stainless Steel T304, T316
  - Galvanized
  - Galvalume Plus

- Thicknesses:
- Aluminum - .016" (.4mm), .020" (.5mm), .024" (.6mm), .032" (.8mm), .040" (1.0mm)
  - Stainless Steel - .010" (.25mm), .016" (.4mm), .020" (.5mm), .024" (.6mm), .032" (.8mm)
  - Galvanized - 30ga, 28ga, 26ga, 24ga, 22ga
  - Galvalume Plus - .016" (.4mm), .020" (.5mm), .024" (.6mm), .032" (.8mm)

Widths: 33" (30" Coverage)

Lengths: 3' to 28' Roll formed  
 12' to 12' 3" Drum corrugated

Colors: Standard colors available (see color chart)  
 Special colors upon request (minimums apply)



**FINISHES**

Smooth or Stucco Embossed

**MOISTURE RETARDER**

For added protection a moisture retarder can be applied to the inside of the metal. (See Moisture Retarder Data Sheet)

